

ITEM DESCRIPTION	WEIGHT (LB)	LONGITUDINAL ARM MOMENT (IN)	LATERAL ARM MOMENT (LB-IN)
79201 CARGO DEPLOYMENT ARM INST'L LH	160-190	0	160-190 IN*LB.
-01 CARGO DEPLOYMENT ARM INST'L LH	12.23	126.0	1541.0 -39.5 -483.1
-02 CARGO DEPLOYMENT ARM INST'L RH	12.23	126.0	1541.0 39.5 483.1

GENERAL INSTALLATION NOTES:

1. INSTALL 79238-01 (PLACARD) AND 79238-02 (PLACARD) IN CLEAR VIEW OF THE PILOT.
2. REMOVAL OF THE CABIN SIDEWARD FACING SEATS IS MANDATORY ON THE SIDE OF THE CARGO DEPLOYMENT ARM INSTALLATION.
3. THE HOOK KNIFE MUST BE CARRIED BY THE RAPPEL OPERATIONS LOAD MASTER FOR IMMEDIATE ACCESS OR FIXED WITHIN THE HELICOPTER CABIN READILY ACCESSIBLE TO THE RAPPEL OPERATIONS LOAD MASTER. THE LOCATION DETAILS OF THE HOOK KNIFE MUST BE DETAILED BY THE OPERATING AGENCY'S OPERATING PROCEDURES.

ADJUST POSITION OF CLAW ADAPTER TO MATCH AIRCRAFT. TIGHTEN TO SECURE THE CLAW ADAPTER (33115) TO THE ROOF STUD AT F.S. 105.1, B.L. 39.5. INSTALL GUARD RINGS AFTER THE CLAW ADAPTER IS SECURE.

SECURE THE "CLAW" ADAPTER (33115) TO THE ROOF STUD AT F.S. 1310, B.L. 39.5. INSTALL GUARD RINGS AFTER THE "CLAW" ADAPTER IS SECURE.

THIS DRAWING CONTAINS INFORMATION AND DATA WHICH IS PROPRIETARY TO AERO DESIGN LTD. THIS DRAWING, OR ANY PORTION THEREOF, MAY NOT BE REPRODUCED, COPIED, OR DUPLICATED IN ANY MANNER, NOR USED FOR MANUFACTURING WITHOUT THE WRITTEN CONSENT OF AERO DESIGN LTD. BY ACCEPTING THIS DRAWING FOR REFERENCE, THE RECIPIENT AGREES TO HOLD AERO DESIGN LTD. HARMLESS FROM THE USE, OR MISUSE, OF THIS DRAWING OR THE INFORMATION CONTAINED THEREIN.

REV.	DESCRIPTION OF CHANGE	INITIAL DATE
0	INITIAL ISSUE	
1	ADDED NOTE 10	RR 27/05/08
2	VARIOUS CHANGES	RR 30/12/08
3	FWD CLAW FITTING ADJUSTABLE	RR 14/04/09
3A	FIX ALTERNATE SCREWS	BJC 23/03/12

